

AQUENCE WL 2042

Known as WOOD-LOK 2042
July 2018

PRODUCT DESCRIPTION

AQUENCE WL 2042 provides the following product characteristics:

Technology	PVA Dispersion
Product Type	Fast Setting Assembly Glue
Application	Assembly
Appearance	white opaque after drying

Application Areas

- Gluing solid wood
- Gluing of blockboard cores and composed solid wood panels
- Assembly and carcass gluing
- Dowel insertion as well as mortice and tenon gluing
- Gluing of laminate sheets to chipboard, block board and the like

Product Properties

- Medium viscosity
- Short setting time
- Gives tough-elastic glue joints
- Workable glue joints
- Highest bonding strength with wood and furniture gluing
- Moisture resistance regarding D2 EN 204

Technical Data

AQUENCE WL 2042:

Minimum film formation temperature, °C (MFFT) DIN 53787	~+5
Viscosity, Brookfield - RVT, 5/20/23, mPa.s ISO 2555	8,500 to 10,500
pH value (20 °C) ISO 976	4.5 to 5.5

DIRECTIONS OF USE

Preliminary Statement

Prior to application it is necessary to read the **Material Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed. Please also refer to the local safety instructions and contact Henkel for analytical support.

Instructions for Use

Open Time

Open time (HPL on chipboard) :	
Quantity applied 100 g/m ² , minutes	~5
Quantity applied 200 g/m ² , minutes	~10

Pressing Time

(at 20°C)	
Surface bonding (Chipboard/HPL) :	
Quantity applied approx. 100 g/m ² , minutes	≥10

Joint bonding (beech/ beech) :	
Quantity applied approx. 150 g/m ² , minutes	≥25

Carcass bonding :	
Quantity applied approx. 150 g/m ² , minutes	≥30

The data shown is based on 8-12 % wood moisture, 20 °C room and material temperature, 65 % relative air humidity and 0.5 N/mm² pressure.

The actual open and setting times will depend heavily on the working conditions such as temperature, humidity and absorption of the wood, surface characteristics, stresses in the material and application thickness of the glue, etc.

The working temperature of the workpiece and glue should be at least +10°C.

Ensure that the parts to be bonded are close fitting and free from dust and grease.

Fit tolerances increase the setting time and reduce the bonding strength.

AQUENCE dispersion glues themselves do not give rise to discoloration of the wood. Metal parts, however, may cause discoloration, due to their reaction with the tannin of the wood (especially with oak).

Usually, application of the glue to one side only is sufficient. Applying glue to both sides, however, is recommended when gluing difficult-to-bond woods and hardwood, in order to improve bonding strength; in this case the open time is increased.

Cleaning

Equipment used to apply the glue may be cleaned easily using cold or luke-warm water before the adhesive has dried hard. Hard dried glue remnants have to be removed mechanically.

STORAGE

Store in the original tightly closed container in a cool, dry place away from frost.
Stir well before use.
Storage life up to 12 months.

Classification:

Please refer to the corresponding **safety data sheets** for details on:

Hazardous Information
Transport Regulations
Safety Regulations

ADDITIONAL INFORMATION**Disclaimer****Note:**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage: [Except as otherwise noted] All trademarks in this document are trademarks and/or registered trademarks of Henkel and its affiliates in the U.S. and elsewhere.

Reference 0.2

Henkel AG & Co. KGaA
73438 Bopfinger, Germany
Phone: +49-7362-81-0

Henkel Corporation
Bridgewater, NJ 08807, USA
Phone: +1-908-685-7000

Henkel (China) Co.Ltd.
201203 Shanghai, China
Phone: +86-21-2891-8000

For more information contact us on www.henkel.com