



BONDERITE® C-AD 9116

Known as Synergic 9116 May 2024

Product description

BONDERITE® C-AD 9116 provides the following product characteristics:

| Technology | Industrial cleaner | |
|--------------|--------------------|--|
| Product type | Additive | |
| Application | Cleaning booster | |

BONDERITE® C-AD 9116 is a neutral liquid cleaning booster.

Application areas:

BONDERITE® C-AD 9116 is used as a degreasing enhancer for all metals in alkaline solutions in immersion processes.

Technical data

| Appearance | Colorless liquid |
|------------|------------------|
| | |

Density, g/cm³ ~1.02 pH (1 % solution) ~5.7

Cold stability, °C down to ~2°C

Directions for use

Preliminary statement:

Prior to use it is necessary to read the **Material Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed. Please also refer to the local safety instructions and contact Henkel for analytical support.

Plant material:

Steel

The concentration and temperature specified in the "Operating Parameters" section must not be exceeded.

Operating data:

Concentration, g/L 5 to 20 of BONDERITE® C-AD 9116

Temperature, °C 45 to 75 Contact time, min 2 to 6

Concentration determination:

It is not possible practically to determine the concentration of BONDERITE® C-AD 9116. As a rule, increasing the concentration is performed together with the cleaning agent in accordance with the stated cleaning agent / degreasing enhancer ratio.

Waste water treatment:

Treatment is carried out in accordance with the official local regulations.

Additional technical parameters:

BONDERITE® C-AD 9116 is also suitable for use in ultrasonic systems.

Recommended concentration, g/L 5 to 20
Temperature, °C 40 to 45
Contact time, min 1 to 3

BONDERITE® C-AD 9116 can also be used as a degreasing enhancer for spraying systems from 65°C upwards.

At some customers we have seen that the usage was possible from 40°C upwards.

Classification:

Please refer to the corresponding Material Safety Data Sheets for details on:

Hazardous Information Transport Regulations Safety Regulations

Storage

Storage of the product is subject to the regulations of Section19 of the German HWH. We will be happy to advise you on this.



Additional information

Disclaimer

The information provided in this Technical data sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. Any liability in respect of the information in the Technical data sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits. The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 2

Henkel AG & Co. KGaA 40191 Düsseldorf, Germany Phone: +49-211-797-0 Henkel Corporation USA Madison Heights, MI 48071 Phone: +1-248-583-9300 Henkel (China) Co. Ltd. 201203 Shanghai, China Phone: +86.21.2891.8000