

BONDERITE L-MR 21718

February 2022

PRODUCT DESCRIPTION

BONDERITE L-MR 21718 provides the following product characteristics:

Technology	Lubricants
Product Type	Water miscible metal working fluids
Application	Metal machining (e.g. turning, drilling, milling, grinding)

BONDERITE L-MR 21718 is a water-miscible, boron free metal working fluid which is free of Cl-, P- and S-containing EP-additives and Formaldehyde Releasing Agents.

The high lubricity of BONDERITE L-MR 21718 extends the tool lifetime and reduces the process costs.

The excellent cleaning performance of BONDERITE L-MR 21718 keeps the machine clean and reduces the maintenance cost.

BONDERITE L-MR 21718 fulfills the rules of the TRGS 611 and is conform to VKIS substance list and contains an inhibitor to prevent the N-Nitrosamine formation.

Application Areas:

BONDERITE L-MR 21718 is a water-miscible cutting fluid for general machining of grey cast iron and different types of steel. The machining of non-ferrous metals is possible in a material mix. For machining of aluminum the compatibility should be checked before use.

BONDERITE L-MR 21718 emulsions are stable and build a very low foaming in a water hardness between 2°GH and 80°GH.

TECHNICAL DATA**(as supplied):**Concentrate:

Density, 20°C, g/cm ³ DIN 51757	0.99
Viscosity, (20°C), mm ² /s DIN 53211	15
Refractive index (20°C)	1,399
Mineral oil content, %	10
Ester oil content, %	0

Emulsion:

Appearance	semi transparent
pH-value, (5%, DI water) DIN 51369	~9.5
Corrosion protection properties, at 5%, DIN 51360-2	0/0

Lubricating effect:

Tapping Torque (7%, 20°GH), Ncm (8 mm, 900 rpm, M4F, AlMgSi1)	30
Reichert (7%, 20°GH), mm² (Ducom Friction test, steel)	15

DIRECTIONS FOR USE**Preliminary Statement:**

Prior to use it is necessary to read the **Material Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed. Please also refer to the local safety instructions and contact Henkel for analytical support.

Dermatological Assessment:

BONDERITE L-MR 21718 can be rated as well tolerated by the skin (Henkel Internal Patch-Test & Skin Irritation Test – OECD 439). Detailed dermatological assessment on request.

Concentration:

Make up concentration: 7 % to 15 %
(depending on the machining operation and material)

Topping up concentration: 1 % to 2 %

Control of the emulsion:Refractometer:

The reading in °Brix multiplied by the product factor 2.0 is equivalent to the concentration in percent.

Titration by pH:

100 mL of the emulsion are titrated down to pH 5.5 using 0.5 N HCl and an electronic pH-meter. The consumption of acid in mL multiplied by the product factor 0.43 is equivalent to the concentration in percent.

Splitting with acid (DIN 51368):

100 mL of the emulsion are heated up with concentrated hydrochloric acid. The reading in mL multiplied by the product factor 3.4 is equivalent to the concentration in percent.

Classification:

Please refer to the corresponding **Material Safety Data**

Sheets for details on:

Hazards identification

Transport information

Regulatory information

Storage:

Recommended Storage Temperature, °C 5 to 40

The shelf life is indicated on the container.

ADDITIONAL INFORMATION**Disclaimer**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 1.3