

CP 27 Aquablock

Universal silicone sealant

FEATURES

Ceresit CP 27 AquaDicht Repair is an universal, low-odour, water-based silicone sealant for repair and sealing work - both indoors and outdoors. The product adheres to wet substrates and old silicone residues. The product is ecological and soluble in water before hardening. Final strength and elasticity are obtained after 3-4 weeks. Adheres to most common construction substrates. UV and weather resistant.



FIELDS OF APPLICATION

For repairing small holes and cracks in tiles, gutters, wall surfaces, water drains, skylights, attics windows and hatches, skylight openings, balconies and terraces. Adheres to most building materials. It is not suitable for use on PE, PP, PTFE (PE - polyethylene, PP - polypropylene, PTFE - polytetrafluoroethylene) oxidation coatings, copper and for underwater use. Due to the large number of possible applications, it is necessary to carry out preliminary tests.

Application mode

Substrates must have load-bearing capacity, must be clean, free of dust and grease. Remove any loose or friable material. Apply the sealant, dip the levelling tool into clean water and level the sealant before a crust forms. This can be levelled in 10 minutes, but always use clean water.

Low temperatures cause a delay of the curing process. Use the sealant in well-ventilated areas to ensure optimal drying conditions. Repairs can be easily carried out when the sealant is still fresh. The required quantities depend on the size of the joints. Immediately after application, clean the tools with clean water and hands with soap and water. Store the product in a cool, dry and frost-free place. For further information please refer to the Data Sheet.

DISPOSAL

Residues of fully cured product = disposal together with household waste / domestic industrial waste. Non-cured product residues must be brought to the municipal waste collection point. Waste code number



European (EWC): 080409. Contains preservatives: thiabendazole

Attention: Causes serious eye irritation.

Keep out of reach of children. If medical advice is required, keep the product container or label close at hand.

IN CASE OF EYE CONTACT:

Rinse gently with water for a few minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. For professional users only.

TECHNICAL DATA

Temperature resistance:	-50 °C to +120 °C
Applying temperature:	+5 °C to +40 °C Max.
width of the gap:	30 mm
Curing speed	2 mm/day
Consumption:	0.5 x width of the gap of (mm) x depth of the gap of (mm) = ml/m ²
Storage time:	approx. 24 months in a cool, dry and frost-free place

PACKAGING

Content 300 ml



Quality for professionals