

# CT 721



## VISAGE 'Wood' Colour Impregnate

Design impregnate reflecting natural wood colours for outdoor and indoor use

### CHARACTERISTICS

- ▶ available in 6 natural wood colours
- ▶ resistant to weather conditions
- ▶ exceptionally durable and resistant to soiling
- ▶ hydrophobic
- ▶ high stability of colour
- ▶ ready to use



### SCOPE OF USE

Ceresit CT 721 impregnate is used for executing a decorative layer with natural wood colours on the surface of Ceresit CT 720 VISAGE 'Wood' Plaster, thin-layer mineral plasters, traditional plasters, concrete and gypsum surfaces. CT 721 impregnate is one of the components used in the external thermal insulation composite Ceresit Ceretherm Visage system for building walls (ETICS) with application of expanded polystyrene boards and mineral wool boards. The material may be sprayed or applied with brush, roller or sponge. The impregnate features exceptional durability and resistance to soiling.

### SUBSTRATE PREPARATION

CT 721 may be used on carrying, dry surfaces, free of substances which decrease adhesion, such as grease, bitumens, dust) :

- CT 720 VISAGE 'Wood' Plaster (age above 3 days)
- Thin-layer mineral plasters (age above 3 days)
- Cement and cement-lime plasters (age above 28 days), concrete (age above 3 months, moisture ≤ 4 %),
- gypsum surface, e.g. decorative plasters (only inside buildings) with moisture below 1 %,
- before application CT 721 substrate should be painted with Ceresit CT 17 priming agent

Moisture pressure from the surface may result in plaster damage, therefore the places exposed to permanent moistness should be provided with appropriate sealing layers.



CERESIT\_C\_CT721V\_TDS\_1\_0318

### APPLICATION

Before use, mix thoroughly the contents of the container. Additionally, make quick mixing movements during application. Do not mix longer than 1 min.

Do not use rusty containers or tools.

Apply the impregnation agent in at least two layers wet on wet.

CT 721 may be sprayed or applied with brush, roller or sponge. Work on one surface should continue uninterrupted, with the impregnation agent of the same batch on each package, or mix the contents of the containers with different batches together.

Thoroughly protect (e.g. with foil) the surfaces which are not to be painted, e.g. windows, doors. Cover shrubs, other plants, etc. Wash accidental stains immediately with plenty of water. Wash tools thoroughly with water right after use.

### PLEASE NOTE

Application should be performed in dry conditions, at air and surface temperature from +5 °C to +25 °C and with relative air humidity below 80 %. The impregnate plaster should be protected against rainfall until it is completely dry. Use covers on scaffolding and building plinths. Do not mix product with other dyes and binding material. Ventilate the rooms after application of impregnate

until odour is no longer perceived, only then can the rooms be released for use. When material comes into contact with the eyes, rinse the eyes with plenty of water and seek medical advice. The product shall be stored in a place inaccessible for children. The performance characteristics are given in the text corresponding to the product Declaration of Performance.

## RECOMMENDATIONS

Do not apply impregnate on walls with high insolation, protect the completed plaster against too fast drying. In case of the damage a decorative coating on 'Wood' plaster, should immediately repaired by re-painting using impregnate CT 721. Opened packages shall be thoroughly closed, and their contents should be used as soon as possible.

## PACKAGING

Plastic containers, 4 l.

Apart from the information given here it is also important to observe the relevant guidelines and regulations of various organisations and trade associations as well as the respective standards of the German Standards Institute (DIN). The aforementioned characteristics are based on practical experience and applied testing. Warranted properties and possible uses which go beyond those warranted in this information sheet require our written confirmation. All data given was obtained at an ambient and material temperature of +23 °C and 50 % relative air humidity unless specified otherwise. Please note that under other climatic conditions hardening can be accelerated or delayed.

The information contained herein, particularly recommendations for the handling and use of our products, is based on our professional experience. As materials and conditions may vary with each intended application, and thus are beyond our sphere of influence, we strongly recommend that in each case sufficient tests are conducted to check the suitability of our products for their intended use. Legal liability cannot be accepted on the basis of the contents of this data sheet or any verbal advice given, unless there is a case of wilful misconduct or gross negligence on our part. This technical data sheet supersedes all previous editions relevant to this product.

## TECHNICAL DATA

Base:	selected silicone oligomers with addition of teflon emulsion
Density:	1.05 kg/dm <sup>3</sup>
Temperature of application:	from +5 °C to +25 °C
Open time:	ca. 30 min.
Resistance to rain:	after ca. 24 h
Impact resistance:	cat. III acc. ETAG 004
Water vapour permeability:	$S_d \leq 1.0$ m acc. ETAG 004
Water absorption after 24 h:	< 0.5 kg/m <sup>2</sup> acc ETAG 004
Adhesion between layers after ageing:	$\geq 0.08$ MPa
Fire classification acc. EN 13501-1:	
A2-s1,d0 in:	Ceresit Ceretherm Universal MW
B – s1, d0 in:	Ceresit Ceretherm Classic, Ceresit Ceretherm Popular Ceresit Ceretherm Wool Classic, Ceresit Ceretherm Visage Ceresit Ceretherm Universal EPS, Ceresit Ceretherm Universal XPS
B – s2, d0 in:	Ceresit Ceretherm Wool Premium
Assumed consumption:	ca. 0.2 – 0.3 l/m <sup>2</sup> at two layers
Available colours:	Iberia Pine Norway Pine Bengal Teak Canada Walnut Congo Wenge Irish Oak

Shelf life/ Storage: Up to 12 months of the production date when stored in cool conditions and in the original, intact packages.

### Protect against freezing! Protect against direct insolation

This product possesses documents of reference:

- European Technical Assessment (ETA) in systems:

Ceresit Ceretherm System	Popular	Classic	Visage	Wool Classic	Wool Premium	Universal EPS	Universal XPS	Universal MW
ETA	08/0309	09/0014	11/0395	09/0026	09/0037	13/0535	13/0807	14/0127
Certificate	1488-CPR-0382/Z	1488-CPR-0439/Z	1488-CPR-0370/Z	1488-CPR-0440/Z	1488-CPR-0375/Z	1488-CPR-0457/Z	1488-CPR-0456/Z	1488-CPR-0362/Z
DoP	00426	00420	00431	00424	00430	00433	00434	00435