



TECHNICAL DATA SHEET

Revision: 06/26/2025
Supersedes: 08/09/2016
Ref. #: 252822

Polyfilla® Wall Tile Grout

DESCRIPTION

LEPAGE® Polyfilla® Polyfilla Wall Tile Grout is a specially formulated water and stain repellent, ready to use grouting compound for ceramic wall tiles. It is recommended for both new ceramic tiling and re-grouting applications. When dry, it forms a hard, long-lasting, waterproof joint between tiles. Polyfilla Wall Tile Grout is siliconized and does not require a grout sealant.

Available as:

Item #	Package	Size
394892	Squeeze tube	162 mL

FEATURES & BENEFITS

- Ready to use, no mixing required
- Fast setting for quick completion of repairs
- Siliconized for improved wet adhesion
- Resistant to water permeation, grout sealer not required
- Stain resistant so it stays white

RECOMMENDED FOR

LePage Polyfilla Wall Tile Grout can be used on ceramic wall tile joints in the tub, shower or kitchen areas. Use to grout newly tiled areas or repair old grouting.

LIMITATIONS

- Not recommended for applications requiring continuous water immersion
- Product should not be diluted with water or solvent
- Not recommended for floor tile grouting or for horizontal surfaces
- Not recommended for joints between tub / shower and ceramic tiles
- Not recommended for joints between counters and tiles
- Not recommended for joints greater than 3 mm (1/8") wide
- Not approved for food contact

TECHNICAL DATA

Typical Uncured Physical Properties

<u>Color:</u>	Off white	<u>Viscosity:</u>	600 to 750 Mcps
<u>Appearance:</u>	Smooth paste (solid)	<u>% Solids:</u>	84%
<u>Base:</u>	Acrylic	<u>pH:</u>	8.0 – 8.8
<u>Odour:</u>	Mild	<u>Specific Gravity:</u>	1.01
<u>Shelf Life:</u>	18 months from date of manufacture (unopened)		
<u>Coverage rate:</u>	0.4m ² to 0.5m ² (10 cm x 10 cm ceramic tiles with 3mm grout lines) <i>Variations in joint width and depth determine the actual application coverage</i>		



TECHNICAL DATA SHEET

Revision: 06/26/2025
Supersedes: 08/09/2016
Ref. #: 252822

TECHNICAL DATA

<u>Lot Code Explanation:</u> (Stamped on crimped end of tube)	YM### Y = Year M = Month ### = Batch # of a product manufactured in that given month and year For example: NE028 N = Year = 2022 E = Month = May 028 = This is the 28 th batch of this product manufactured in May 2022	<table><tr><th>Year</th><th></th><th>Month</th><th></th></tr><tr><td>2020</td><td>K</td><td>January</td><td>A</td></tr><tr><td>2021</td><td>M</td><td>February</td><td>B</td></tr><tr><td>2022</td><td>N</td><td>March</td><td>C</td></tr><tr><td>2023</td><td>P</td><td>April</td><td>D</td></tr><tr><td>2024</td><td>R</td><td>May</td><td>E</td></tr><tr><td>2025</td><td>S</td><td>June</td><td>F</td></tr><tr><td>2026</td><td>T</td><td>July</td><td>G</td></tr><tr><td>2027</td><td>W</td><td>August</td><td>H</td></tr><tr><td>2028</td><td>X</td><td>September</td><td>J</td></tr><tr><td>2029</td><td>Y</td><td>October</td><td>K</td></tr><tr><td>2030</td><td>A</td><td>November</td><td>M</td></tr><tr><td>2031</td><td>B</td><td>December</td><td>N</td></tr></table>	Year		Month		2020	K	January	A	2021	M	February	B	2022	N	March	C	2023	P	April	D	2024	R	May	E	2025	S	June	F	2026	T	July	G	2027	W	August	H	2028	X	September	J	2029	Y	October	K	2030	A	November	M	2031	B	December	N
Year		Month																																																				
2020	K	January	A																																																			
2021	M	February	B																																																			
2022	N	March	C																																																			
2023	P	April	D																																																			
2024	R	May	E																																																			
2025	S	June	F																																																			
2026	T	July	G																																																			
2027	W	August	H																																																			
2028	X	September	J																																																			
2029	Y	October	K																																																			
2030	A	November	M																																																			
2031	B	December	N																																																			
Note: I, L, O, Q, U, V, and Z have been skipped																																																						

Typical Application Properties

Application Temperature: Apply and cure above 10°C (50°F)

Open Time: 15 minutes*

Dry Time: 24 to 48 hours*

* *Varies based on temperature, humidity, and fill depth*

Typical Cured Performance Properties

Colour: Off white

Paintable: Yes

Cured Form: Hard non-flexible solid

Water Resistant: Yes, after fully cured

Water Resistant: Yes, after fully cured

Chemical Resistant: Resistant to harsh cleaners

DIRECTIONS

Tools Typically Required:

Rubber float, sponges and cloth

Safety Precautions:

Wear gloves, safety glasses, and wash hands after use.

Preparation:

Apply and cure above 10°C (50°F). Grout joints must be clean, dry and free of grease, dust and other contaminants. Tile adhesive should be fully cured. The presence of debris, old grout, spacers or excess tile adhesive can result in uneven colour and poor adhesion. Not suitable for joints wider than 3 mm (1/8"). To repair any air pockets or cracks, reapply more tile grout once the initial application is fully cured. If using the squeeze tube, remove the cap and trim the tip to desired bead size.

Application:

Compact grout into joints uniformly using a hard rubber float, working diagonally across the joints. It is important to work and finish small areas at a time. Apply and remove excess grout with a damp sponge within 15 minutes after application. Allow the grout to set for another 15 minutes then remove remaining grout residue diagonally across the surface with a damp sponge until it appears clean. For rough or textured tiles, apply and remove excess in even smaller areas at a time. When grout is firm in about 1 hour, polish away surface film with a clean, dry cloth. Cures hard in 24 hours.

Clean-up:

Clean hands immediately with water. Clean tools with warm, soapy water within one hour of use.



TECHNICAL DATA SHEET

Revision: 06/26/2025
Supersedes: 08/09/2016
Ref. #: 252822

STORAGE & DISPOSAL

DAMAGED BY FREEZING. Store above freezing. Store tightly sealed to prevent drying. Product should not be washed down drain, to avoid clogging. To dispose of unwanted product, squeeze out from tube or scrape out from tub, allow to harden, and discard with trash. Wipe/rinse container and place with plastics for recycling.

LABEL PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN.

Refer to the Safety Data Sheet (SDS) for further information

DISCLAIMER

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Henkel recommends purchasers/users should test the products to determine acceptable quality and suitability for the intended use. All adhesive/sealant applications should be tested under simulated or actual end use conditions to ensure the adhesive/sealant meets or exceeds all required project specifications. Since assembly conditions may be critical to adhesive/sealant performance, it is also recommended that testing be performed on specimens assembled under simulated or actual production conditions. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the patent

LIMITED WARRANTY

This product is warranted by Henkel Corporation to be free from defects in materials when used as directed. Henkel's sole obligation shall be, at its option, to replace or refund the purchase price of product proven to be defective. Henkel makes no other warranty – express or implied – including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE and will not be liable for consequential or incidental damages. This Limited Warranty gives you specific legal rights, which vary from state to state. For warranty assistance, contact Henkel at 1.800.624.7767 M-F 9:00 am to 4:00 pm ET.



LEPAGE® Brand is part of the Henkel family of brands. Founded in 1876, Henkel is a global leader in the consumer and industrial businesses. Henkel operates worldwide with leading brands and technologies in three business areas: Laundry & Home Care, Beauty Care and Adhesive Technologies.

Henkel Canada Corporation - Professional & Consumer Adhesives Headquarters - Mississauga, ON L5N 6C3

www.henkel-northamerica.com



For Technical Assistance call: 1-800-624-7767 – Mon-Fri - 9:00a – 4:00p ET

www.lepage.ca