

# LOCTITE<sup>®</sup> 5004™

February 2008

## PRODUCT DESCRIPTION

LOCTITE<sup>®</sup> 5004™ provides the following product characteristics:

<b>Technology</b>	Solvent based
<b>Chemical Type</b>	uPVC in solvent
<b>Appearance</b>	white
<b>Solvent</b>	THF Methylethylketone Cyclohexanone
<b>Components</b>	One part - requires no mixing
<b>Viscosity</b>	Medium
<b>Cure</b>	Solvent evaporation
<b>Application</b>	Bonding of uPVC pipes & fittings

LOCTITE<sup>®</sup> 5004™ is a special solvent based adhesive for bonding uPVC pipes. It is specially formulated to meet the requirements for contact with drinking water laid down by the German Health Authorities.

This product is suitable for joints resistant to shear strain of pressure pipes with uPVC fittings (water and gas) in accordance with recommendations of the Plastic Pipe Association

## Approvals

LOCTITE<sup>®</sup> 5004™ complies with DIN 16970 and KRV guideline R1.17. and the rules for construction and testing of drainage pipes. It also complies with the adhesives standards BS 4326, part 3, ASTM D2564 and NEN 7106.

The Cured adhesive meets the requirements of admission for drinking water supply through mPVC pipes in compliance with the recommendation number VIII of the Plastics Commission of the Bundesgesundheitsamt (German Health Authorities).

## TYPICAL PROPERTIES OF UNCURED MATERIAL

Specific Gravity @ 25 °C	0.96
Viscosity, Epprecht @ 23 °C, mPa·s (cP):	
Epprecht Body 3	2,500
Flash Point - See SDS	

## TYPICAL CURING PERFORMANCE

Assembly joints should not be moved within 5 minutes of assembly. Pressure testing should not take place before 24 hours after assembly.

## GENERAL INFORMATION

**This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected as a sealant for chlorine or other strong oxidizing materials.**

**For safe handling information on this product, consult the Safety Data Sheet (SDS).**

## Directions for use:

1. Adhesive should be applied lightly to the socket and liberally to the pipe, which should be immediately inserted into the socket (within 4 minutes at 20°C). At higher temperatures this open time should be reduced (e.g. to 1 minute at 40°C).
2. Parts must not be moved within 5 minutes after assembly at 20°C.
3. However, at lower temperatures longer waiting times should be allowed.

## Not for product specifications

The technical data contained herein are intended as reference only. Please contact your local quality department for assistance and recommendations on specifications for this product.

## Storage

Store product in the unopened container in a dry location. Storage information may be indicated on the product container labeling.

**Optimal Storage: 8 °C to 21 °C. Storage below 8 °C or greater than 28 °C can adversely affect product properties.**

Material removed from containers may be contaminated during use. Do not return product to the original container. Henkel Corporation cannot assume responsibility for product which has been contaminated or stored under conditions other than those previously indicated. If additional information is required, please contact your local Technical Service Center or Customer Service Representative.

## Conversions

(°C x 1.8) + 32 = °F
kV/mm x 25.4 = V/mil
mm / 25.4 = inches
µm / 25.4 = mil
N x 0.225 = lb
N/mm x 5.71 = lb/in
N/mm <sup>2</sup> x 145 = psi
MPa x 145 = psi
N·m x 8.851 = lb·in
N·m x 0.738 = lb·ft
N·mm x 0.142 = oz·in
mPa·s = cP

## Note:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as

differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

**In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:**

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

**In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

**In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:**

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

#### **Trademark usage**

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 0.2