

Description

Loctite® Frekote® 4368 is an all-purpose, silicone based release agent. It contains a special lubricant, which provides optimum release along with surface conditioning on any metal or plastic mold. Loctite® Frekote® 4368 works equally well with epoxies, polyurethanes and polyesters in room temperature or elevated cure systems.

Features

Use with room temperature or elevated cure systems
Excellent slip
Multi-purpose release

Properties

Appearance	Clear Liquid
Odor	Hydrocarbon Odor
Solvents	Hexane
Specific Gravity	0.72
Shelf Life	18 months from date of manufacture

Mold Preparation

The mold surface must be clean and free of any release agent or other contaminants for Loctite® Frekote® 4368 to be completely effective. Remove any contaminants with Loctite® Frekote® PMC or another suitable cleaning solvent. Light industrial abrasives can be used to remove heavy resin build up.

Application *Consult MSDS Prior To Use*

1. Apply Loctite® Frekote® 4368 by brushing or spraying. Allow solvents to evaporate (5 to 10 minutes) leaving a thin release film on the mold.
2. For optimum finish on the cast parts, the dry film may be buffed lightly with a soft cloth.
3. Repeat the cycle on each succeeding part.

Flammability/Storage

Loctite® Frekote® 4368 contains flammable solvents. The product should always be used in well ventilated areas. Consult MSDS for complete details.

Note

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended

applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada, Inc. the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.