

# Glue Remover

## DESCRIPTION

LOCTITE® Glue Remover is a solvent-based product developed to help remove instant adhesives. It is designed for home use and helps in the removal of cured Super Glue (cyanoacrylate) residues from stained or badly bonded objects. The Glue Remover is suitable for use on vertical surfaces and non-porous surfaces and does not attack most surface materials and plastics. It can also be effective in removing marker or ink stains on most surfaces except fabrics..

### Available as:

Item #	Package	Size
3076845	Metal Tube Carded Blister	5 g (0.18 oz)

## FEATURES & BENEFITS

- Helps remove and cleanup excess glue from surfaces
- Works on many substrates
- No drip gel consistency
- Self-piercing tube

## RECOMMENDED FOR

LOCTITE Glue Remover works to help de-bond glued items, remove and clean excess glue from surfaces, such as, glass, metal, ceramic, stone, and some plastics.

*\*Always test in an inconspicuous area to confirm remover will not harm surfaces or materials*

## LIMITATIONS

- Do not use on painted or varnished surfaces.
- Not suitable for use on some hard plastics e.g. ABS.
- Test on a hidden area before use if in any doubt
- Not suitable for use on fabrics or carpet. Will cause discoloration

## TECHNICAL DATA

Typical Physical Properties		Typical Application Properties	
<u>Color:</u>	Clear/ Colorless	<u>Application Temperature:</u>	Use between 50°F (10°C) and 80°F (27°C)
<u>Appearance:</u>	Gel	<u>Odor:</u>	Mild solvent (use in a well-ventilated area)
<u>Base:</u>	Propylene Carbonate	<u>Shelf life:</u>	24 months (unopened)
<u>Flash Point:</u>	> 123 °C (> 253.4 °F)	<u>Lot Code Explanation:</u>	XYDDD (printed on crimped end of tube) X = Disregard Y = Last digit of year of manufacture DDD = Day of manufacture based on 365 days in a year
<u>Shelf Life:</u>	From date of manufacture (unopened): 24 months	Example: X5061 = 61 <sup>st</sup> day of 2025 = March 2, 2025	

**DIRECTIONS****Tools Typically Required:**

Absorbent pads or tissue.

**Safety Precautions:**

Use in a well-ventilated area. Wear gloves and wash hands after use.

**Preparation:**

Test a small amount of glue remover on an inconspicuous area to guarantee solvent does not harm surface.

**NOTE:** Remover may damage certain plastics, dull or mar paints, or discolor dyed fabrics or carpets.

**Application:**

Screw down the cap / nozzle assembly onto the tube to puncture the seal (do not squeeze tube) and remove cap carefully. Apply sufficient LOCTITE Glue Remover to cover the glue residue or stain. Place a pad of absorbent material/tissue on top of the remover. Leave for several hours or preferably overnight. Remove and discard the absorbent pad/tissue, which will now contain the dissolved glue residue. Wipe the area with a clean cloth. Rinse with water and allow to dry. Repeat the process if required.

**Clean up:**

Soap and water.

**STORAGE & DISPOSAL**

**Not damaged by freezing.** Store in a cool, dry location with cap tightly secured on tube. Use an approved hazardous waste facility for disposal.

**LABEL PRECAUTIONS****CAUTION! MAY CAUSE EYE IRRITATION**

**CAUTION!** Contains propylene carbonate. May cause eye irritation. Avoid contact with eyes. Do not swallow. Use with adequate ventilation. DO NOT TAKE INTERNALLY. Wash thoroughly after handling. **FIRST AID:** For eye contact, flush with water for 15 minutes, call a physician. For skin contact or if spilled on clothing, flush with large quantities of water. For ingestion do not induce vomiting, call a physician. For skin contact wash thoroughly with soap and water. **KEEP OUT OF THE REACH OF CHILDREN.**



WARNING! Cancer - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

Refer to the Safety Data Sheet (SDS) for further information

**DISCLAIMER**

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Henkel recommends purchasers/users should test the products to determine acceptable quality and suitability for the intended use. All adhesive/sealant applications should be tested under simulated or actual end use conditions to ensure the adhesive/sealant meets or exceeds all required project specifications. Since assembly conditions may be critical to adhesive/sealant performance, it is also recommended that testing be performed on specimens assembled under simulated or actual production conditions. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

**LIMITED WARRANTY**

This product is warranted by Henkel Corporation to be free from defects in materials when used as directed. Henkel's sole obligation shall be, at its option, to replace or refund the purchase price of product proven to be defective. Henkel makes no other warranty – express or implied – including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE and will not be liable for consequential or incidental damages. This Limited Warranty gives you specific legal rights, which vary from state to state. For warranty assistance, contact Henkel at 1.800.624.7767 M-F 9:00 am to 4:00 pm EST.



# Technical Data Sheet

Revision: September 15, 2025  
Supersedes: New  
Ref. #: 173026



## Trusted Performance. Proven Results.

For over 50 years, LOCTITE Brand adhesives and sealants have taken on the toughest jobs. Used in race cars, airplanes, and even in the space-shuttle, LOCTITE provides solutions for the most demanding industrial, professional and consumer applications. LOCTITE gives you the specialization, power, and performance to not only get your job done, but to get it done right.

For Technical Assistance call : 1-800-624-7767 – Mon-Fri 9:00a – 4:00p ET  
[www.loctiteproducts.com](http://www.loctiteproducts.com)



LOCTITE Brand is part of the Henkel family of brands. Founded in 1876, Henkel is a global leader in the consumer and industrial businesses. Henkel operates worldwide with leading brands and technologies in three business areas: Laundry & Home Care, Beauty Care (Consumer Brands) and Adhesive Technologies.

Henkel Corporation - Professional & Consumer Adhesives Headquarters - Rocky Hill, CT 06067  
[www.henkel-northamerica.com](http://www.henkel-northamerica.com)