



Technical Data Sheet



Technical Data Sheet
Ref: NRLO23000TDS
Issued: 06/10/25
Number of pages: 02

Glue Remover

CHARACTERISTICS

LOCTITE® Glue Remover is a solvent based product, designed for the removal of instant adhesives.

It is designed for home use and removes cured Super Glue from stained or badly bonded objects. It is also effective on many other types of glue. LOCTITE® Glue Remover is a powerful solvent for cured Super Glue (cyanoacrylate) residues, yet does not attack most surfaces, plastics and materials.

LOCTITE® Glue Remover is suitable for use on vertical surfaces, non-porous surfaces. It can also be effective in removing marker or ink stains.



INSTRUCTIONS FOR USE

1. Perform a test in an inconspicuous area to ensure suitability.
2. Apply sufficient LOCTITE® Glue Remover to cover the glue residue or stain.
3. Place a pad of absorbent material/tissue on top of the Remover. If the residue/stain is on fabric, place a tissue on both sides of the material.
4. Leave for several hours or preferably overnight.
5. Remove and discard the absorbent pad/tissue, which will now contain the dissolved glue residue.
6. Wipe the area with a clean cloth. Rinse with water and allow to dry.
7. Repeat the process if required.



TECHNICAL DATA

Composition	Propylene carbonate
Appearance	Clear gel
Density	1.209 g/cm ³ @ 20 °C
Viscosity	Non-drip gel
Pack	3g tube
Safety	See Safety Data Sheet
Shelf Life at 20 °C	24 months unopened
Shelf Life at 2-8 °C	24 months unopened

LIMITATIONS

- ☐ Do not use on painted or varnished surfaces.
- ☐ Not suitable for use on some hard plastics e.g. ABS.
- ☐ Test on a hidden area before use if in any doubt.
- ☐ When used on skin, for external use only. Avoid contact with eyes.

STORAGE

Store in a cool, dry place, out of reach of children.

HEALTH AND SAFETY

Before using the product please see related Material Safety Data Sheet that is available on request.

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

Henkel Norden AB

Box 1155, SE-172 23

Sundbyberg

SE: Tel. +46 10 480 75 00, DK: Tlf +45 4330 1300, NO: Tlf. +47 2337 1520, FI: Puh. +358 20 122 311

Consumer service

SE: Tel. 010 480 7601, DK: Tlf. 80 88 77 05, NO: Tlf. 800 191 00, FI: Puh. 0800 165 066

Consumerservice-ac.norden@henkel.com