

PRODUCT DESCRIPTION

LOCTITE® PC 3967 Stripped Thread Repair Kit consists of a two-component, gray and blue repair material and a one-component release agent. LOCTITE® PC 3967 can be used to repair stripped threaded assemblies in a variety of metal and wood.

TYPICAL APPLICATIONS

LOCTITE® PC 3967 can be used to repair damaged threaded metal assemblies. Typical applications include threaded assemblies on oil pans, valve covers, distributor caps transmission pans and housing.

PRODUCT FEATURES

Easy to Use:

- One kit repairs all sizes
- Requires no machine shop skills
- Repairs typical assemblies not possible by other means.

Fast, Reliable, Versatile:

- Works on a wide range of materials
- Achieves handling strength in 5 minutes
- Achieves full strength in two hours
- Cures to machinable hardness in two hours

Safe to use:

- Non-flammable

PROPERTIES OF UNCURED MATERIAL

Repair Material

	Typical Value
Chemical Type	Dimethacrylate Ester
Appearance	Gray, mixed
Odor	Mild pungent
Specific Gravity	1.57
Flash Point, °F	>200

Release Agent (liquid)

	Typical Value
Chemical Type	Silicone Emulsion
Appearance	Blue
Odor	None
Flash Point	None

MAXIMUM TORQUE VALUES FOR REPAIRED THREADS

Bolt Type	Bolt Size				
	1/4	5/16	3/8	7/16	1/2
English Inches Grade 5					
Metric mm Grade 8.8	6	8	10	11	12
Max. Recommended Torque (in.lbs)	23	45	82	129	193

Bolt Type	Bolt Size				
	9/16	5/8	3/4	7/8	1
English Inches Grade 5					
Metric mm Grade 8.8	14	16	19	22	25
Max. Recommended Torque (in.lbs)	273	375	648	1080	1538

TECHNICAL DATA

LOCTITE® PC 3967 is a high-technology chemical system that restores threads to damaged fastener assemblies. The prime advantage of Loctite's system is the fact that LOCTITE® PC 3967 repairs almost all common fastener sizes and thread grades. LOCTITE® PC 3967 is used on most metals (aluminum, iron, steel, brass, magnesium, copper, etc.)

GENERAL INFORMATION

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected as a sealant for chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).

Where aqueous washing systems are used to clean the surfaces before bonding, it is important to check for compatibility of the washing solution with the adhesive. In some cases these aqueous washes can affect the cure and performance of the adhesive.

This product is not normally recommended for use on plastics (particularly thermoplastic materials where stress cracking of the plastic could result). It is recommended to confirm compatibility of the product with such substrates.

Directions for use

1. Coat bolt with release agent.
2. Dispense and mix equal amounts LOCTITE® PC 3967 compounds on clean surface.
3. Apply into application.
4. Screw bolt into place.
5. Wait 5 minutes and remove bolt.
6. Allow compound to cure for 30 minutes before use.

Storage

Store product in unopened container in a cool dry location. Ideal conditions are within the range 8 to 21 degrees C (46 to 70 degrees F) and are recommended for long term storage. Exposure to higher temperatures (greater than 28 degrees C) for prolonged periods should be avoided as extended exposure

to warm conditions can adversely affect product properties. For further specific shelf life information, contact your local Technical Service Center.

Note

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada, Inc. the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is not liable for the suitability of our product for the

production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.