



LOCTITE® SF 7263 CHAIN LUBE

April 2025

Product description

LOCTITE® SF 7263 CHAIN LUBE provides the following product characteristics:

| | |
|-------------------|--|
| Technology | Aerosol |
| Chemical Type | Lubricating oil |
| Appearance | Clear liquid |
| Cure | Not applicable |
| Application | Chain lube |
| Specific benefits | <ul style="list-style-type: none">• Foaming action permits fast, deep penetration with reduced amount of run off.• Protects parts exposed to harmful or corrosive elements - lubricates, protects and prolongs the life of gears, chains, cables and wire rope.• Repels dirt, sand and dust leaving the chain clean and minimizing wear on the gear, chain or cable.• Formulated with additives that reduce the "throwoff" from centrifugal force - reduces the frequency of repeat applications.• Does not contain CFC. |

LOCTITE® SF 7263 CHAIN LUBE is a clear, oily spray lubricant that protects and prolongs the life of gears, chains and wire rope. Once applied, active material easily penetrates into the most important parts of chains and fittings, where it forms a lubricating film offering long-lasting surface protection. This ideal lubricant prolongs the life of the chain by reducing friction, wear, noise and vibration.

Application areas

LOCTITE® SF 7263 CHAIN LUBE typical applications include chain-driven equipment - chain, pin, roller and bushing areas. Sprockets, open gears, wire rope, pulleys, snatch blocks, hoists, conveyors, fork lifts, elevators, overhead door drives, mining, construction, earthmoving and material handling equipment.

Technical data

| | |
|-------------------------|---------------------------------|
| Colour | Colourless |
| Odour | Chracteristic solvents |
| Specific gravity @ 27°C | 0.92 to 0.98 gm/cm ³ |
| In service temperature | 5 to 35°C |
| Flash point | 140°C |
| Boiling point | 250°C |
| Aerosol propellant | LPG |

GENERAL INFORMATION

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected as a sealant for chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Safety Data Sheet (SDS).

Directions for use:

1. Shake can before use.
 2. Spray liberally on parts as required.
 3. Repeat if necessary.
 4. Product sprays best at room temperature.
- Application**
1. Application area should be free of any source of ignition.
 2. Shake the can well before using.
 3. Product sprays best at room temperature.
 4. Generously spray gear, chain, cable or wire rope with lubricant and allow 5 to 10 minutes for complete penetration before operation.
 5. Cables and ropes should be completely saturated to ensure protection against corrosion.
 6. Regular use will aid in achieving longer life and improved performance.

Note: Do not apply while parts are moving.



Handling precautions

Prior to use LOCTITE® SF 7263 CHAIN LUBE use gloves, goggles and barrier cream. Avoid contact with skin. Ensure adequate ventilation during application. For further details refer Material Safety Data Sheet.

Storage

Store product in the unopened container in a dry location. Storage information may be indicated on the product container labeling.

Optimal Storage: 8°C to 21°C. Storage below 8°C or greater than 28°C can adversely affect product properties.

Material removed from containers may be contaminated during use. Do not return product to the original container. Henkel Corporation cannot assume responsibility for product which has been contaminated or stored under conditions other than those previously indicated. If additional information is required, please contact your local Henkel representative.

The expiry date of the product is given on the packaging labels.

Product Specification

The technical data contained herein are intended as reference only and are not considered specifications for the product.

Product specifications are located on the Certificate of Analysis or please contact Henkel representative.

Approval and Certificate

Please contact Henkel representative for related approval or certificate of this product.

Data ranges

The data contained herein may be reported as a typical value. Values are based on actual test data and are verified on a periodic basis.

Temperature/Humidity Ranges: 23°C / 50% RH = 23±2°C / 50±5% RH

Conversions

(°C x 1.8) + 32 = °F
 kV/mm x 25.4 = V/mil
 mm / 25.4 = inches
 µm / 25.4 = mil
 N x 0.225 = lb
 N/mm x 5.71 = lb/in
 N/mm² x 145 = psi
 MPa x 145 = psi
 N·m x 8.851 = lb·in
 N·m x 0.738 = lb·ft
 N·mm x 0.142 = oz·in
 mPa·s = cP

Disclaimer

The information provided in this Technical data sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. Any liability in respect of the information in the Technical data sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 1