

POLYFILLER

Permanent repair filler for plaster, brick, stone and wood

Filler for plaster, brick, stone, wood, before painting or other finishes.

USES

- ▶ Skimming expanded polystyrene and asbestos for easy painting
- ▶ For filling cracks in wood work, defective paint work and gaps between floor boards
- ▶ Mixed with mineral wool, it can be used for pipe lagging
- ▶ As sculpting and modeling material
- ▶ For fixing plaster board panels



fast setting

DESCRIPTION

Polyfiller is permanent repair to plaster, brick, stone, wood etc, before painting or other finishes. Polyfiller provides a smooth finish

ADVANTAGES

- long working time
- excellent adhesion to most building materials
- easy to use- just add water
- provides good finish

TECHNICAL SPECIFICATION

Working time (hrs) : 1 ½

Setting time (hrs) : 2 ½

SUPPLY

Polyfiller : 1.5kg packs

STORAGE & SHELF LIFE

Store under cover, out of direct sunlight and protect from extreme temperature. In tropical climate the product must be stored in air-conditioned environment. Shelf life is up to 12 months when stored as per recommendations.



TDS_Polyfiller_RTL_1116

1

HEALTH & SAFETY

As with all construction chemical products caution should be always be exercised. Protective clothing such as gloves and goggles should be worn. Treat any splashes to the skin or eyes with fresh water immediately. Should any of the products be accidentally swallowed, do not induce vomiting, but call for medical assistance immediately



Henkel Polybit Industries Ltd.

PO Box: 293, Umm Al Quwain, UAE

Phone: +971 (6) 76 70 777; Fax: +971 (6) 76 70 197

henkelpolybit@henkelpolybit.com; www.henkelpolybit.com

Apart from the information given here it is also important to observe the relevant guidelines and regulations of various organisations and trade associations as well as the respective standards. The aforementioned characteristics are based on practical experience and applied testing. Warranted properties and possible uses which go beyond those warranted in this information sheet require our written confirmation. All data given was obtained at an ambient and material temperature of +23°C and 50 % relative air humidity at laboratory conditions unless specified otherwise. Please note that under other climatic conditions hardening can be accelerated or delayed.

The information contained herein, particularly recommendations for the handling and use of our products, is based on our professional experience. As materials and conditions may vary with each intended application, and thus are beyond our sphere of influence, we strongly recommend that in each case sufficient tests are conducted to check the suitability of our products for their intended use. Legal liability cannot be accepted on the basis of the contents of this data sheet or any verbal advice given, unless there is a case of wilful misconduct or gross negligence on our part. This technical data sheet supersedes all previous editions relevant to this product.

Quality for Professionals