



PRITT

ALLESKLEBER

Technical Data Sheet v.1, July 2026

Water-based multi-purpose glue

CHARACTERISTICS

- Water-based multi-purpose glue for crafting and hobby
- Transparent
- Solvent free
- Washable
- Easy application bottle: dot and line application
- Suitable for cardboard, paper, photo paper, wood, cork, leather and many others (not suitable for plastics)

APPLICATION FIELD

- Multi-purpose adhesive for home, kindergarten, school and office
- Ideal for crafting and hobby

INSTRUCTION FOR USE

Pretreatment

Clean the material surface before gluing. Best bonding strength will be achieved if surface is dry and free from dust and grease. Very smooth surfaces should be roughened with sandpaper.

Application

Apply a thin layer of PRITT Multipurpose Glue onto one side, join and fix the pieces together. Drying time depends on applied glue quantity, temperature, humidity and substrate. Scarce use of glue leads to faster drying. Porous substrates like paper and cardboard dry faster than non-porous ones like coated papers, foils, plastics or metals. Humid weather extends drying time.

Only in the case of two non-porous surfaces bring the parts together, separate and leave them to partly dry for approximately 10 minutes and rejoin them.



TECHNICAL DATA

Composition	Water-based adhesive
Density, g/cm ³	ca. 1.05
pH value	5 - 6
Viscosity, mPa.s (cP)	2500 - 3500
Shelf life (at ambient temperature), months	12



LIMITATIONS

Storage

Keep tightly closed and store in a dry and cool place. Avoid temperatures below 5°C and above 35°C.

Packaging

Article abbreviation	Color	Container	IDH
PRD15	Transparent	Bottle 150g	2999296

DISPOSAL

Small dried quantities can be disposed of as household/commercial waste. Dispose of large quantities separately. Empty packaging should be recycled. The European waste code can be found in the Safety Data Sheet.

HEALTH AND SAFETY

It is recommended to consult the current safety data sheet for precautions and safety advice before starting processing. The safety data sheet is available at www.mysds.henkel.com. For Information for allergy sufferers on Tel. 0049 (0)211 797 0 (keyword emergency)



The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

Henkel AG & Co. KGaA

Henkelstr. 67, D-40589 Düsseldorf,
P.O. Box, D-40191 Düsseldorf
Phone: +49 (0) 211 / 797-0
E-Mail: produkt-info-klebstoffe@henkel.com
Internet: www.prittworld.de

Henkel CEE GmbH

Erdbergstraße 29
A-1030 Wien
Phone: +43 (1) 71104-0

Henkel & Cie. AG

Aeschengraben 29
CH-4051 Basel
Phone: +41 (0) 61 / 825-7000
Internet: www.prittworld.ch

