



PRITT

ALLESKLEBER

Technical Data Sheet v.4, June 2026

CHARACTERISTICS

- Water based, clear, washable, polyvinyl alcohol based adhesive
- Solvent free
- Can be completely washed out of fabrics at 20°C

APPLICATION FIELD

- Suitable for sticking a wide range of art and craft materials including paper, card, fabric, wood and pasta



INSTRUCTIONS FOR USE

Pretreatment
Not necessary. In general, surfaces have to be clean, dry and free of dust and grease.

TECHNICAL DATA

Composition	Water, polyvinyl alcohol, antifoam and preservative
Appearance	Clear, viscous liquid
Solids content, %	15 - 20
Temperature range, °C	5 - 35
Cure type	Water evaporation
Open time, minutes*	Up to 10, dependent of type and porosity of substrates to be bonded
Setting time, hours*	1 - 2, dependent of type and porosity of substrates to be bonded. Fully dry within 24 hours.
Colour	Clear
Shelf life at 20°C, months	12

*parameter depends on ambient temperature, moisture content and thickness (characteristic) of the materials.

LIMITATIONS

Not suitable for bonding plastics or for bonding non-porous surfaces to non-porous surfaces.
May wrinkle very thin decorative papers and vellum.
Should only be applied to clean, dry surfaces free of dust, grease, polish and moisture.

Storage
Keep tightly closed and store in a dry and cool place between 5 - 35°C.



HEALTH AND SAFETY

Before using the product please see related Safety Data Sheet that is available on request.

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

Henkel Limited

Wood Lane End, Hemel Hempstead, Hertfordshire HP2
4RQ
Phone: +44 (0) 1606 593 933
Internet: www.henkel.co.uk
email: technical.services@henkel.co.uk

