



Technical Data Sheet



Technical Data Sheet
Ref: NRPTR9000
Issued: 07/10/2025
Number of pages: 2

Pritt ECO Flex Correction Roller

PRODUCT DESCRIPTION:

The ECO Flex Correction Roller has a 100% recycled plastic housing and offers an ergonomic sideways application with a flexible nib. The corrected area can be overwritten without any drying time. The optimised correction layer shows outstanding smear resistance and coverage properties.



TECHNICAL PRODUCT DESCRIPTION:

Injection moulded plastic parts

The ECO Flex Correction Roller has a 100% recycled plastic housing

Tape

- Siliconised polyester carrier
- Synthetic resin with titanium dioxide, cover up layer combined with a polyacrylate based adhesive

CHARACTERISTICS:

- Ergonomic sideways format and flexible applicator it adapts to the application angle and goes on smoothly and cleanly Immediate coverage of nearly all types of writing, prints and drawings
- Two-way correction: pull for a whole sentence, push for one letter. Good adhesion on smooth and nearly smooth surfaces
- Cover up layer needs no drying time and can be overwritten with all common inks, pens and machines
- No smearing of water based inks on the cover up layer while overwriting
- No shadows on copies
- Writing tips or printing heads will not be damaged when applied correctly
- Protective cap
- Solvent free

INSTRUCTIONS FOR USE:



Place paper/material to be corrected on a smooth, flat and steady surface.

Position the roller – printed side up – at a 45° angle over text to be corrected. Apply a light, but firm pressure on the roller nib and pull or push the roller over the surface you wish to correct. Make sure of putting the application nib flat on the surface at every application. For a clean break, stop and lift up at a slight angle.

If the cover up layer should not stick properly to the paper, i.e. on critical coated papers the film may be finished with light pressure with your finger.

TECHNICAL DATA

Tape length	10m
Tape width	4.2mm
Shelf Life	2 years from date of manufacture @20°C

LIMITATIONS

Storage

Store in a dry and cool place. Avoid temperatures over 50°C.

HEALTH AND SAFETY

Before using the product please see related Material Safety Data Sheet that is available on request.

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

Henkel Norden AB

Box 1155, SE-172 23

Sundbyberg

SE: Tel. +46 10 480 75 00, DK: Tlf +45 4330 1300, NO: Tlf. +47 2337 1520, FI: Puh. +358 20 122 311

Consumer service

SE: Tel. 010 480 7601, DK: Tlf. 80 88 77 05, NO: Tlf. 800 191 00, FI: Puh. 0800 165 066

Consumerservice-ac.norden@henkel.com