



# Technical Data Sheet



## Pritt Multi Tac

### CHARACTERISTICS

A permanently pliable, pressure sensitive, low tack multi-purpose putty for mounting and securing lightweight items around the home, office, school, workshop etc.:

- Strong hold
- Repositionable
- Reusable
- Clean removal

### APPLICATION FIELD

Pritt Multi Tac mounts posters, hangs decorations and greetings cards, secures small items such as ornaments, telephones and desk accessories.

### INSTRUCTIONS FOR USE

1. Make sure surfaces to be bonded are sound, dry, clean and free from dust and grease.
2. Remove a small piece of tack from the sheet and work
3. Work between fingers to soften
4. Apply to one surface to be bonded, mount and press down firmly

### TECHNICAL DATA

<b>Composition</b>	Blend of synthetic rubber, fillers and mineral oil
<b>Appearance</b>	Sheet of white putty with indentations at 10mm centres
<b>Curing system</b>	Non-curing
<b>Odour</b>	None
<b>Adhesion</b>	Excellent to most substrates
<b>Temperature</b>	Should not be stored or used at temperatures above 30°C or below 5°C
<b>Durability</b>	At normal room temperature and humidity, adhesive bonds will remain permanently pliable indefinitely
<b>Rheology</b>	Pliable putty
<b>Shelf life</b>	12 months from date of manufacture

Technical Data Sheet

Ref: PR23000

Issued: 13.10.22

Number of pages: 2





## **PACKAGING**

Carboard wallet containing 35g sheet of Tack

## **LIMITATIONS**

Do not use on absorbent surfaces such as bare plaster, brick work etc. as surfaces are prone to staining

Removal not recommended for porous or delicate surfaces such as uncoated wallpapers and fibrous papers.

Care should be taken when removing the tack, particularly if it has been stuck for a long time. Use a small piece of tack to remove remaining traces.

## **HEALTH AND SAFETY**

Before using the product please see related Material Safety Data Sheet that is available to download from [mymds.henkel.com](http://mymds.henkel.com).

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

## **Henkel Limited**

Wood Lane End, Hemel Hempstead, Hertfordshire HP2 4RQ

Phone: +44 (0) 1606 593 933

Internet: [www.henkel.co.uk](http://www.henkel.co.uk)

e.mail: [technical.services@henkel.co.uk](mailto:technical.services@henkel.co.uk)