



# Technical Data Sheet



Technical Data Sheet  
Ref: SE8000  
Issued: 13.10.22  
Number of pages: 2

## Sellotape Parcel Plus Tape

### CHARACTERISTICS

- Super sticky
- Extra thick
- Non splitting

### PRODUCT DESCRIPTION

Sellotape Parcel Plus Tape is based on a clear BOPP (biaxially oriented polypropylene) film coated with a clear or brown pigmented pressure sensitive acrylic adhesive.

### TECHNICAL DATA (TYPICAL)

Colours	Clear & Brown
Thickness	60µm
Tensile strength	50 N/cm
Elongation at break	135%
Peel adhesion	4 N/cm

### APPLICATION

Sellotape Parcel Plus Tape is tough and waterproof with a strong adhesive.

It supports parcels to withstand rough handling in the post.



**Packaging:**

Retail B2C (Brown only):  
Shrinkwrap with disc label  
Tower 3 rolls

B2B (Clear and Brown):  
Shrinkwrap towers of 5 rolls

**Roll sizes:**

Retail:  
48mm x 50mm (Brown only)

B2B:  
50mm x 66m (Clear and Brown)

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

**Henkel Limited**

Wood Lane End, Hemel Hempstead, Hertfordshire HP2 4RQ  
Phone: +44 (0) 1606 593 933  
Internet: [www.henkel.co.uk](http://www.henkel.co.uk)  
e.mail: [technical.services@henkel.co.uk](mailto:technical.services@henkel.co.uk)