

TECHNOMELT AS 5303

Known as Technomelt Q 5303
December 2022

PRODUCT DESCRIPTION

TECHNOMELT AS 5303 provides the following product characteristics:

Technology	Polyolefin
Product Type	Hotmelt
Appearance	Light beige

TECHNOMELT AS 5303 is a thermoplastic hotmelt adhesive, based on Polyolefines.

Application Areas:

TECHNOMELT AS 5303 is used for assembly applications, especially for bonding of polypropylen and other polyolefines.

TECHNICAL DATA

(as supplied)

Colour	light beige
Solid content, %	100
Softening point, °C (R&B) ASTM E 28	118 to 130
Viscosity Brookfield, Spindle 27 at 180°C, mPa.s ASTM D 3236	3,200 to 5,200
at 190°C, mPa.s ASTM D 3236	2,000 to 3,400
Application temperature, °C	170 to 200

DIRECTIONS FOR USE

Preliminary Statement:

Prior to use it is necessary to read the **Material Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed. Please also refer to the local safety instructions and contact Henkel for analytical support.

Preparation:

The substrates must be dry, free of oil, grease and dust.

Application:

TECHNOMELT AS 5303 is applied by melting equipment with gear pump.

The usual processing range is between 160 to 200°C.

While processing, take care to maintain a gentle thermal load by keeping the recommended working temperature range, because overheating or too often repeated melting may cause quality changes in the adhesive.

The stated processing temperatures are standard values which, according to the processing method, may vary within certain limits.

Apply the adhesive as closely as possible to the site where the parts to be bonded are joined and in a thickness ensuring complete and intensive contact to both surfaces.

When the materials which are bonded have different adhesion properties apply the adhesive to the surface which is more difficult to bond.

If this is not possible, it is recommended to increase the application temperature and/or the thickness of the adhesive layer applied.

Immediately after joining, keep the parts together until the bonded join is held by the adhesive itself.

The required fixing time is depending on the recovery force of the material to be bonded, the "hot tack" and the solidification properties of the adhesive.

Cleaning:

For the cleaning of the application equipment we recommend to use our TECHNOMELT 1960.



Storage:

Frost-sensitive	no
Recommended storage temperature, °C	10 to 35
Shelf-life, months (in unopened original packaging)	24

Classification:

Please refer to the corresponding **Material Safety Data**

Sheets for details on:

- Hazards identification**
- Transport information**
- Regulatory information**

ADDITIONAL INFORMATION**Disclaimer**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation or

Henkel Canada, Inc.the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 0.0

