

TECHNOMELT® PUR 9011

December 2023

Product description

TECHNOMELT® PUR 9011 provides the following product characteristics:

Technology	Polyurethane
Application	Lamination
Appearance	Translucent

Product properties

TECHNOMELT® PUR 9011 is a 100%-solids, moisture-curing hot melt adhesive designed to provide excellent adhesion to PVC along with a relatively low viscosity and extended open time. TECHNOMELT® PUR 9011 contains UV dye for improved visibility under an UV light source. TECHNOMELT® PUR 9011 has shown outstanding adhesion to different types of PVC, and this can be enhanced by use of an appropriate water-based primer.

Technical data

TECHNOMELT® PUR 9011:

Solids content, %	100
Viscosity, mPa.s (cP) at 250°F	Approx. 7000
Open time, minutes	Approx. 3 - 4

Open time will vary depending to a large extent on the thermal conductivity of the substrate being coated. With surfaces that are good insulators (such as wood, foamed plastics and high pressure laminate), the open time may be extended; while with metals, open time may be shortened.

Directions for use

Preliminary statement

Prior to use it is necessary to read the **Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed. Please also refer to the local safety instructions and contact Henkel for analytical support.

Application

TECHNOMELT® PUR 9011 can be applied by spray, roll coater, or slot coater adapted for reactive hot melts at material temperature of approximately 250°F.

Panel bonding

Apply TECHNOMELT® PUR 9011 to one substrate at about 6 - 10 grams/square foot. Assemble parts and pass through a nip roller or cold press for 5 seconds and then dead stack overnight.

Vinyl laminating

Coat either the vinyl film or the other substrate at 1.5 to 2.0 wet mils. A handling bond develops immediately after nipping or pressing.

Processing

Reactive hotmelt adhesives have a limited thermal stability even when working at the specified working temperatures. Therefore, we recommend that a period of 4 hours without production, that the unit is either switched off, or the set temperatures on the unit be reduced to 60 °C.

Application temperature

Recommended application temperature is 250 - 275°F.

Depending on the processing and performance needs of the application, temperatures may vary. However, Adhesive temperatures above 300°F should be avoided. NOTE: Use only with adequate forced ventilation. READ PRECAUTIONS BEFORE USING ADHESIVE.

Curing

Full cure will take place in approximately 3 - 7days.

Curing is accomplished through reaction with moisture. The moisture can be provided by the substrate, through absorption from the atmosphere, or a combination of both. Under extremely dry conditions a light water-mist will help the cure. High temperatures accelerate curing.

Cleaning

Henkel offers a selection of TECHNOMELT®PUR Cleaners to facilitate the removal of curedand uncured materials. To clean hoses and nozzles, use TECHNOMELT®PUR Cleaner 2, Cleaner 4, Cleaner MEor Cleaner All-In-One. To clean uncured material from the rolls of roll coaters, use Cleaner785A. To facilitate removal of cured material from the rolls of roll coaters, use Cleaner 7. TECHNOMELT®PUR Cleaner 3030 and M-O-C may be used to remove uncured hot melt from surfaces. Some cured material may require removal by mechanical means or the use of a special solvent for removal (e.g., n-methyl pyrroli-done) if necessary.

Handling Information

This product contains isocyanate. Read SDS before handling and using this product. Store in a dry area at 60 - 95°F. Use only in equipment in-tended for reactive hot melts. Do not use in conventional hot melt equipment. Forced ventilation must be provided over applicator and melting equipment to remove any small amount of isocyanate vapors to the outside. All users of RHM products should maintain an ongoing industrial hygiene program. This program should include contingency provisions in the event of ventilation failure as well as MDI monitoring.

Storage

Rotate stock and use oldest material first. Do not expose to the atmosphere or otherwise contaminate with moisture. Moisture contamination will cause a sharp melt viscosity increase and a cured skin on top of the container. Containers must be used completely after opening. Do not attempt to reseal.

Shelf life

Shelf-life (in unopened original packaging), months 9
(at 77°F)

Classification

Please refer to the corresponding **Safety Data Sheet** for details on:

Hazardous Information
Transport Regulations
Safety Regulations

Additional information

Disclaimer

The information provided in this Technical data sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. Any liability in respect of the information in the Technical data sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 1

Henkel AG & Co. KGaA 73438 Bopfinger, Germany Phone: +49-7362-81-0	Henkel Corporation Bridgewater, NJ 08807, USA Phone: +1-908-685-7000	Henkel Diadema Diadema - SP, Brasil Phone: +55-11-3205-8955	Henkel (China) Co.Ltd. 201203 Shanghai, China Phone: +86-21-2891-8000	Henkel Jebel Ali FZCO Dubai, UAE Phone: +971-4-3893333
--	--	---	---	--

For more information, please contact us on www.henkel.com