

TEROSON RB 2451

November 2020

PRODUCT DESCRIPTION

Technology	Rubber
Product Type	Preformed Parts
Additional Information	Permanent plastic

TEROSON RB 2451 is a permanent plastic butyl sealer based on non reactive rubbers. It stays tacky and permanent plastic also after passing the EC-oven. TEROSON RB 2451 strongly adheres to many surfaces, such as plastics, metal alloys and also to oiled metal sheets. The material also retains its plastic properties at low temperatures without getting brittle or flaking off. It offers excellent sealing and corrosion protection.

APPLICATION AREAS

TEROSON RB 2451 is primarily used for sealing joints and overlapped gaps in the automotive industry and by its component suppliers. It is also used in the appliance manufacture (e.g. dish washers).

TECHNICAL DATA:

Colour	black
Odour	none
Density	1.5 g/cm ³
Solids	>98 %
Viscosity	approx.80 1/10 mm
Needle	ASTM D5, 5 s, 100 g
Temperature	20 °C
Corrosion resistance	no loss of adhesion, no corrosion
Resistance to aging in Cataplasma	no loss of adhesion, no corrosion
In service temperature range:	-40 to 120 °C
Temperature resistance	200 °C
Application temperature	room temperature

PRELIMINARY STATEMENT

Prior to use it is necessary to read the **Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed.

APPLICATION

To get sufficient adhesion, the adhesive must be slightly pressed on. We recommend to remove the release paper after the pressing. This ensures an unwanted stretching of the strip. Finally the countersurface is pressed on and the entire part has to be mechanically fixed.

Classification:

Please refer to the corresponding **Material Safety Data Sheets** for details on:

Hazards identification

Transport information

Regulatory information

Storage:

Frost sensitive	no
Recommended storage temperature	5 to 35 °C
Shelf life	24 months

Disclaimer

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned

herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 1.0