

Teroson RB 274

July 2013

PRODUCT DESCRIPTION

Teroson RB 274 provides the following product characteristics:

Technology	Butyl Rubber
Product Type	Sealant
Application	Assembly
Appearance	White
Consistency	Plastic, Adhering

Teroson RB 274 is a white, high quality, pressure sensitive sealing tape based on butyl rubber with plasto-elastic properties and high recovery.

The material demonstrates good aging resistance and extensive UV resistance as well as strong tackiness.

Application Areas:

Teroson RB 274 is mainly used in the manufacture of caravans for sealing outer panelling overlaps, decorative and covering trims as well as rubber mouldings against the outer panelling. Larger mouldings should additionally be fixed mechanically despite of the strong tackiness of Teroson RB 274.

TECHNICAL DATA

Density, g/cm ³ :	approx. 1.45
Solids, %:	100
Penetration (cone 150 g, 6 s, 23°C), mm:	approx. 50 1/10
Cold flow:	none
Paint compatibility:	can be painted
In service temperature range, °C:	-40 to 90
Short exposure (up to 1 h), °C:	200

DIRECTIONS OF USE

Preliminary statement:

Prior to application it is necessary to read the **Material Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed.

Pre-Treatment:

The substrates must be clean, dry, oil and grease free.

Application:

Teroson RB 274 is cut to the required length and then applied to the mouldings and profiles to be sealed and lightly pressed on. We recommend to leave the release paper on the sealing strip as protection against contamination. In addition, an unwanted stretching of the strip during unrolling can be prevented. Prior to mounting the coated parts the release paper will be pulled off, the parts are put on, evenly pressed on and mechanically fixed.

STORAGE

Frost-Sensitive	No
Recommended Storage Temperature, °C	5 to 35
Shelf-life (in unopened original packaging), 24 months	

ADDITIONAL INFORMATION

Note:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of

Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 0.0

