

# Teroson RB 2759

July 2013

## PRODUCT DESCRIPTION

Teroson RB 2759 provides the following product characteristics:

<b>Technology</b>	Butyl Rubber
<b>Product Type</b>	Sealant
<b>Application</b>	Assembly
<b>Appearance</b>	Grey

Teroson RB 2759 is a high quality, gun-grade, one component sealant based on butyl rubber with a low solvent content.

After evaporation of the solvents a permanent plastic, aging- and weather-resistant material with good sealing function remains. Complete curing depends on ambient temperature and layer thickness. Any excess material can be simply dabbed off after curing.

Until complete evaporation of the solvents volume contraction must be expected with Teroson RB 2759 as with all solvent containing products.

## Application Areas:

Teroson RB 2759 is used for the following applications:

- Sealing of front-, rear-, side- and hinged window between rubber/glass and rubber/metal
- Sealing of polyester plates / aluminium rails at shower cubicals
- Sealing of metal overlaps and decorative moldings in the manufacture of car bodywork and caravans

## TECHNICAL DATA

Density, g/cm <sup>3</sup> :	approx. 1.4
Consistency:	pasty
Solids, %:	87
Pressure viscosity, g:	approx. 50
Measuring System:	Extrusion viscometer
Nozzle, mm ø:	4
Pressure, bar:	2
Flow time, sec.:	30
Temperature, °C:	20
Sag resistance:	good
Application temperature:	room temperature
In service temperature range, °C:	-30 to 80
Short exposure (up to 1 h), °C:	100

## DIRECTIONS OF USE

### Preliminary statement:

Prior to application it is necessary to read the **Material Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed.

### Pre-Treatment:

As far as possible the substrates must be clean, dry, free of oil and grease. Small traces of oil and fat can be absorbed by Teroson RB 2759.

### Application:

The processing out of nozzle cartridges or plastic wallets happens by use of common air pressure pistols or hand guns. For compressed air pistols 3 to 4 bar are needed. The material should be either applied between the parts to be sealed or to one side and then covered with the other part.

Any excess material can be simply dabbed off either by using Teroson RB 2759 or any other plastic material, e.g. Teroson II or -VII.

### Notice

Considerable stringing will occur as long as the material still contains solvents. Therefore you should wait for a sufficient period or remove major excess quantities with a spatula. Residues can be dabbed off immediately thereafter.

## STORAGE

Frost-Sensitive	No
Recommended Storage Temperature, °C	10 to 25
Shelf-life (in unopened original packaging), 12 months	

## ADDITIONAL INFORMATION

### Note:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

**In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:**

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

**In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

**In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:**

The data contained herein are furnished for information only and are believed

to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

**Trademark usage**

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 0.0