

## TEROSON® RB 4006

July 2013

### PRODUCT DESCRIPTION

TEROSON® RB 4006 provides the following product characteristics:

<b>Technology</b>	Butyl Rubber
<b>Product Type</b>	Sealant
<b>Application</b>	Assembly
<b>Appearance</b>	Grey

TEROSON® RB 4006 is a high quality, gun-grade, one component sealant based on butyl rubber with a low solvent content. After evaporation of the solvents, TEROSON® RB 4006 represents a tough plastic, extrudable, deformable sealing mass. The complete drying depends on the ambient temperature and on the applied layer thickness. Due to its deformability TEROSON® RB 4006 should only be used for sealing of gaps with little or no movement. TEROSON® RB 4006 is suitable for the sealing of inner and outer joints. The product can be applied on horizontal as well as on vertical areas without draining off.

#### Application Areas:

TEROSON® RB 4006 is mainly used for the sealing of sheet metal and plastic overlaps i.e. in the field of caravan, motor home industry or air controlling / ventilation technology.

### TECHNICAL DATA

Density, g/cm³	approx. 1.4
Consistency:	pasty
Solids, %:	approx. 85
Skin formation time, min*:	approx. 20 to 30 (after application)
Setting time, weeks:	1 to 2
Sag resistance:	very good
Acceptable deformation, %:	<5
In service temperature range, °C:	-20 to 80
* DIN 50014 standard climate:	23°C, 50% relative air humidity

### DIRECTIONS FOR USE

#### Preliminary Statement:

Prior to application it is necessary to read the **Material Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed.

#### Pre-Treatment:

The substrates must be clean, dry, oil and grease free. For cleaning we recommend Cleaner A, D and FL.

#### Application:

The processing of 310-ml-cartridges is carried out by a hand- or air pressure pistol. For compressed air pistols, a pressure of 2 to 5 bar is needed, depending on the nozzle cross section and processing speed. For the processing of TEROSON® RB 4006 out of hobbocks, processing equipment with extrusion pumps is needed (minimum pressure conversion 30:1).

#### Cleaning:

TEROSON® RB 4006 can be removed by knife or spatula. The remaining layer can be washed off with Cleaner FL or a cleaning solvent.

#### Storage:

Frost-Sensitive	No
Recommended storage temperature, °C	5 to 30
Shelf-life (in unopened packaging), months	original 12

### ADDITIONAL INFORMATION

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

**In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:**

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

**In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

**In case products are delivered by Henkel Corporation, or Henkel Canada Corporation, the following disclaimer is applicable:**

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved



in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

**Trademark usage**

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 0.0

