

TEROSON RB H378

Known as Bondmaster H378
January 2023

PRODUCT DESCRIPTION

TEROSON RB H378 provides the following product characteristics:

Technology	Assembly
Product Type	Hot applied sealant for tightness

Automotive headlamps assembly: glass or polycarbonate lenses to non treated polypropylene housing. For any other substrate, please ask for our technical advice. TEROSON RB H378 allows to re-open the sealed joints, e.g. for service, repair or recycling.

TECHNICAL DATA

Colour	black or grey
Viscosity Brookfield RV 8 (spindle 28, speed 2.5 rpm)	180°C, approx. 200,000 mPa.s
Density, g/cm ³	approx. 1.2

Shear strength on polypropylene samples (shear speed 100 mm/min) : approx. 0.3 MPa

Adhesion to polycarbonate:

- After 72 hours ageing at room T°C : good
- After 72 hours at - 40°C : good
- After 72 hours in water at 60°C : good
- After 72 hours at 80°C : good

DIRECTIONS FOR USE

Preliminary Statement:

Prior to use it is necessary to read the **Material Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed.

Operating Conditions:

Apply by standard melter (type Nordson serial MX) or by bulk melter with heated plate.

Temperature of application: 170 - 190°C. During any interval in working, the temperature should be reduced.

Extrude product into headlamp channel and assemble lens rapidly to ensure a good wetting of the two substrates.

Do not mix with other products.

For any other application conditions, please ask for our technical advice.

Caution:

The final results can be affected if the substrates are not clean.

Cleaning:

Please consult us.

Precautions:

The product is applied hot: take all the safety precautions to avoid splashing and contact with skin.

Provide an efficient ventilation to avoid hot melt fumes.

Classification:

Please refer to the corresponding **Material Safety Data Sheets** for details on:

Hazards identification
Transport information
Regulatory information

Storage:

Frost sensitive	no
Recommended storage temperature, °C	5 to 35
Shelf- life, months (in original packaging)	24

ADDITIONAL INFORMATION

Disclaimer

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 0.1

Henkel AG & Co. KGaA
40191 Düsseldorf, Germany
Phone: +49-211-797-0

Henkel Corporation USA
Madison Heights, MI 48071
Phone: +1-248-583-9300

Henkel (China) Co. Ltd.
201203 Shanghai, China
+86.21.2891.8000

For more information, please contact us on www.henkel.com