

TEROSON VR 170

Known as Cold Clean

July 2014

PRODUCT DESCRIPTION

TEROSON VR 170 provides the following characteristics:

Technology	Cold Cleaner for cleaning and degreasing of engines and mechanical components
Base	Organic Solvents
Additional Information	free from chlorinated and aromatic solvents

TEROSON VR 170 is a multi-purpose, solvent based cleaning product for cleaning and degreasing of mechanical components such as engines and engine components. TEROSON VR 170 does not attack automotive paints once the paint has been fully dried. The cleaner is designed in a way that it can be easily rinsed off with water, the water/oil-grease mixture however can be easily separated in standard oil separating systems to reduce industrial waste. TEROSON VR 170 does not contain any chlorinated or aromatic solvents.

APPLICATION AREAS

TEROSON VR 170 can be used for all cleaning and degreasing applications where oil and grease has to be removed from cars, engines, engine components etc.

TECHNICAL DATA

(Typical Test Results)

Colour	clear, colourless
Odour	mild
Consistency	liquid
Density	approx. 0.8 g/cm ³

PRELIMINARY STATEMENT

Prior to application it is necessary to read the **Material Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed.

Application

TEROSON VR 170 can be used in all standard cleaning processes. When TEROSON VR 170 is used in pressure cleaners, the manufacturers recommendations have to be observed. For best results, spray a sufficient amount of TEROSON VR 170 directly onto the parts to be cleaned. For heavily contaminated components, cleaning performance can be enhanced by additionally using a brush. After a soaking time of 5 - 10 minutes, TEROSON VR 170 should be rinsed off with strong water jet or a steam cleaner.

Caution

TEROSON VR 170 should be used together with oil separator systems. For best separation results, TEROSON VR 170 must not be used together with other emulsifying agents as used in car wash's for instance, as the oil/water separation will be dramatically reduced. Due to the strong degreasing properties of TEROSON VR 170 prolonged skin contact should be avoided.

STORAGE

Frost sensitive	no
Recommended storage temperature	10 to 25 °C
Shelf life	24 months



TEROSON VR 170

Known as Cold Clean

July 2014

Disclaimer

Note:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Henkel AG & Co. KGaA

D-40191 Düsseldorf, Germany

Phone: +49-211-797-0

www.henkel.com

Henkel Central Eastern Europe GmbH

A-1030 Wien, Austria

Phone: +43-1711-040

www.henkel.com

Henkel & Cie AG

CH-4133 Pratteln, Switzerland

Phone: +41-61-825-7000

www.henkel.com

