

## TEROSON VR 50

January 2020

### PRODUCT DESCRIPTION

TEROSON VR 50 provides the following characteristics:

|                   |                                                                       |
|-------------------|-----------------------------------------------------------------------|
| <b>Technology</b> | Thinner and pretreatment product for bonding and sealing applications |
| <b>Base</b>       | Organic Solvents                                                      |

TEROSON VR 50 is a liquid universal pretreatment product. The product is a mixture of aromatic free organic solvents. It contains no chlorinated hydrocarbons; it is not harmful to car paints when used on a short-term basis.

### Application Areas:

TEROSON VR 50 is mainly used for pretreatment of substrates prior to application of adhesives and sealants. Accurate pretreatment of surfaces is essential for a perfect adhesion. Depending on the basis of the adhesives and sealants TEROSON VR 50 can also be used for removing of tools and contaminated surfaces.

### TECHNICAL DATA

(Typical Test Results)

|          |                                |
|----------|--------------------------------|
| Colour:  | transparent                    |
| Odour    | of organic solvents            |
| Density: | approx. 0.82 g/cm <sup>3</sup> |

### PRELIMINARY STATEMENT:

Prior to use it is necessary to read the **Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed.

### Application:

Depending on the degree of contamination, size and shape of the parts to be treated, TEROSON VR 50 is applied and wiped off with a non-woven tissue or the like. To prevent contamination of the contents in the original packaging, the product should either be poured onto the tissue (Attention: Do not press the tissue against the opening and invert of the container!) or transfer to another clean container (metal can or the like). Dispense only the required amount and then reclose the original container immediately.

The pretreated surface must be allowed to dry completely before applying the adhesive or sealant.

### Storage:

|                                 |            |
|---------------------------------|------------|
| Frost sensitive                 | no         |
| Recommended storage temperature | 5 to 25 °C |
| Shelf life                      | 12 months  |

### Disclaimer

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

**In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:**

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

**In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

**In case products are delivered by Henkel Corporation, or Henkel Canada Corporation, the following disclaimer is applicable:**

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.



**Trademark usage**

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

**Henkel AG & Co. KGaA**

D-40191 Düsseldorf, Germany  
Phone: +49-211-797-0  
www.henkel.com

**Henkel Central Eastern Europe GmbH**

A-1030 Wien, Austria  
Phone: +43-1711-040  
www.henkel.com

**Henkel & Cie AG**

CH-4133 Pratteln, Switzerland  
Phone: +41-61-825-7000  
www.henkel.com

