

TEROSON WX 980

Known as Wax Underbody Coating Spray

May 2014

PRODUCT DESCRIPTION

TEROSON WX 980 provides the following product characteristics:

Application	Anticorrosive Agent for Vehicle Underbodies
Technology	Solvent Containing Anticorrosive Agent for the Care, Touch Up and Repair of Factory-Applied Underbody Coating
Basis	Wax

TEROSON WX 980 is a solvent containing, bitumen free anticorrosive agent based on wax, polymers and anticorrosive additives. The product can be precision and exhibits excellent sag resistance. It is fast drying, and even in a thin layer thickness it forms a closed water protecting film. The dry film shows good adhesion and anticorrosive properties.

APPLICATION AREAS

TEROSON WX 980 is primarily used on wax coated vehicle underbodies and particularly for the secondary treatment of all protective coatings, like those based on PVC, PVC/wax, bitumen/rubber and rubber/resins. In addition the material has proven successful for the following application areas:

- secondary treatment of inaccessible areas, such as corners, edges, seams etc. where rust spots are preferably formed
- addition of existing coating materials based on PVC, bitumen/rubber, rubber/resins and wax
- for selective applications and for repair coating of all underbodies after an accident

TECHNICAL DATA

(Typical Test Results)

Colour	anthracite
Odour	characteristic odour, like wax, mild
Density	approx. 0.97 g/cm ³
Layer thickness dry film (2-3 crossing patterns)	10 to 200 µm
Drying time	approx. 2 hrs. dust dry
Behaviour in the cold	no cracking, no flaking off

Storage	8 hrs -25 °C
Mandrel	70 mm Ø
Condensed water containing constant climate test DIN 50017-KK	min 400 hrs. without rust
Temperature resistance	no sagging up to 100 °C
Application temperature	10 to 25 °C
In service temperature	-25 to 80 °C
Short exposure (up to 1 h)	100 °C

PRELIMINARY STATEMENT

Prior to application it is necessary to read the **Material Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed.

Pretreatment

Surfaces to be treated with TEROSON WX 980 have to be cleaned well and rust must be removed. The areas must be dry and grease, dirt and dust free. In the case of new vehicles, protective wax must be steam-cleaned. If applied to older vehicles, watch out for beginning of rust formation, which has to be removed with a wire brush.

Application

TEROSON WX 980 should have room temperature at time of application. Shake can well, continuing for 1 minute after the ball-bearing becomes audible. Hold can vertically while spraying and apply at a distance of about 20 to 30 cm. Abrasion resistance and corrosion protection increase with the layer thickness. For this reason spraying should be repeated once or twice after a short drying time. In order to avoid bare patches, the material should be sprayed in criss-cross fashion.

After use the can should be held with the valve down and the spray should be activated until the jet is cleared and only propellant is emitted.

TEROSON WX 980

Known as Wax Underbody Coating Spray

May 2014

Note

Do not spray on moveable parts and those subjected to extreme heat, e.g. joints, engine, drive, cardan shaft, exhaust, catalyst and brake system.

Cleaning

Remove overspray immediately with white spirit or TEROSON VR 10.

STORAGE

Frost sensitive	no
Recommended storage temperature	10 to 20 °C; (protect from temperatures over 50 °C!)
Shelf life	18 months

Disclaimer**Note:**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Henkel AG & Co. KGaA

D-40191 Düsseldorf, Germany
Phone: +49-211-797-0
www.henkel.com

Henkel Central Eastern Europe GmbH

A-1030 Wien, Austria
Phone: +43-1711-040
www.henkel.com

Henkel & Cie AG

CH-4133 Pratteln, Switzerland
Phone: +41-61-825-7000
www.henkel.com

