



Technical Data Sheet



Technical Data Sheet
Ref: US30000
Issued: 23.03.23
Number of pages: 3

Indoor Fill & Repair Sealant

CHARACTERISTICS

- Easy to apply and tool.
- Clean up with water.
- Paintable from 1 hour
- Good adhesion to most common household surfaces
- Low odour
- Solvent-free
- Traditional cartridge and Easy Pulse Convenient air powered dispenser (no cartridge gun required) packaging formats.

APPLICATION FIELDS

A one-component, ready to use sealant, based on an acrylic dispersion. Ideal for filling indoor connecting joints where some movement is expected prior to painting.

STANDARDS

- Conforms to BS EN 15651-1
 - BS EN 15301-1
- Product type F- INT: Façade sealant for interior application
Reaction to fire: Class E



**TECHNICAL DATA:****Uncured product**

Base:	Acrylate dispersion, water based	
Odour:	Characteristic	
Application temperature:	+5°C - +40°C (substrate and ambient)	
Consistency:	Non-slump paste	
Density:	~1,61 g/cm ³	(ISO 2811-1)
Resistance to flow:	~ 0 mm	(ISO 7390)
Skin formation time:	~ 25 minutes	(23°C, 50% r.h.)
Curing speed:	~ 10 days/5 mm	(23°C, 50% r.h., bead 20x10mm)

Cured product

Odour:	Odourless	
Shore A hardness:	~ 35	(ISO 868)
100% Modulus:	~ 0,2 N/mm ²	(ISO 8339-A)
Elongation at break:	~ 100%	(ISO 8339-A)
Shrinkage:	~ -28%	(ISO 10563)
Movement capability:	12,5 %	
Recommended joint width:	max. 30 mm	
Service temperature:	-20°C - +80°C	

INSTRUCTIONS FOR USE**Surface preparation**

All surfaces must be clean, dry, and free from contaminants likely to impair adhesion.

Sealant application

The sealant should be applied ensuring that the joint is completely filled. Smooth off the sealant with a UniBond Sealant Smoothing Tool to ensure good contact between the sealant and the bonding surfaces. Clean up excess sealant with a damp cloth immediately.

Cleaning tools

Fresh sealant can be cleaned with a cloth dampened with water.

Cured sealant can only be removed by mechanical means (e. g. knife or razor blade)

Please note:

Over paintable from 1 hour dependent on joint width and ambient conditions. Fully cured in 24 hours

LIMITATIONS.

Not suitable for exterior use or areas subject to damp.

Only for use as an interior joint sealant in areas where some movement is expected.

Not recommended for repairing gaps or cracks in walls.

Not suitable for areas of constant immersion or permanent damp (e.g., Aquariums or swimming pools).

Do not use on natural stone (e.g., marble, granite)

This product is not sand able.



If in doubt, contact our technical helpline for further assistance.

GENERAL INFORMATION

Storage

Store in a cool, dry place between +5 °C and +25 °C. Shelf life is 18 months in an unopened dispenser after date of manufacture (the expiry date is shown on the dispenser).

Packaging.

Easy Pulse pressure pack – 330g

Cartridge - 462g

Colours

White

HEALTH AND SAFETY

Before using the product please see related Material Safety Data Sheet that is available to download from mysds.henkel.com.

“The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.”

Henkel Limited

Wood Lane End, Hemel Hempstead, Hertfordshire, HP2 4RQ

Phone: +44 (0) 1606 593 933

Internet: www.henkel.co.uk

email: technical.services@henkel.co.uk