



# Technical Data Sheet



Technical Data Sheet  
Ref: TA8000  
Issued: 22/11/2023  
Number of pages: 3

## UniBond Masking Tape *Easy on Easy off*



### CHARACTERISTICS

High quality masking tape for professional results with brush or spray  
Presents bleed through giving super sharp paint lines  
3 Days resistance to sunlight when used on window frames etc.  
Gives Sharp edges to paintwork  
Easy to tear

### APPLICATION FIELD

- Ideal for interior masking of window frames, skirting boards, intricate decorating, walls\*, doors, cornices, and coving.
- Suitable for plaster, paint, varnish, wood, glass, metal, and most plastics.

### INSTRUCTIONS FOR USE

#### Application

- 1) Clean – apply only to clean, dry and sound surfaces which are free from dust, oil, grease and polish
- 2) Apply, smooth down with fingers and paint.
- 3) Remove within 3 days. For emulsion paint always remove immediately after painting in order to avoid paint bleed.



## TECHNICAL DATA

Colour	Off white
Carrier material	Saturated crepe paper
Adhesive	Synthetic rubber resin – solvent free
Width	25 mm, 38 mm
Length	25 m
Total thickness	Approx. 105 µm
Total weight	77 g/m <sup>2</sup>
Tensile strength (PSTC-31)	Approx. 36 N/cm
Elongation at break	7 %
180°Peel adhesion on steel (PSTC-1)	5 N/cm
Temperature resistance	+60 °C (1 hour)
Application temperature	+10°C to +30°C
Shelf life	12 months from date of manufacture, stored in cool, dry conditions

## LIMITATIONS

Not suitable for exterior use

**\*Do not** use on wallpaper or other delicate surfaces.

## Important

Always remove within 3 days. Tapes may damage surfaces, always test the area first before use.

## Storage

Store in a dry place between 15 C° and 25 °C. Protect product from direct sunlight.

## Packaging

25mm x 25m and 38mm x 25m rolls on 3" cardboard core packed in a cardboard cuff

## HEALTH AND SAFETY

Before using the product, please see related Material Safety Data Sheet that is available on request.

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.



**Henkel Limited**

Wood Lane End Hemel Hempstead, Herts HP2 4RQ

Phone: +44 (0) 1606 593 933

Internet: [www.henkel.co.uk](http://www.henkel.co.uk)

email: [technical.services@henkel.co.uk](mailto:technical.services@henkel.co.uk)