



Technical Data Sheet



Technical Data Sheet
Ref:US40000
Issued: 30.03.2023
Number of pages: 2

UniBond Multi-Purpose 2 in 1 Sealant Remover & Smoother Tool

CHARACTERISTICS

UniBond Sealant Remover and Smoother Tool is a 2 in 1 tough, fibreglass reinforced plastic tool which has a sharp end for the removal of all types of sealants from all surfaces, without damaging the surface or surrounding tiles and, a flat end to provide three sealant smoothing profiles to produce a perfect finish.

APPLICATIONS

UniBond Sealant Remover & Smoother Tool can be used for:

- Removal of all types of cured sealant from all surfaces
- Smoothing of applied sealant beads before curing

TECHNICAL DATA

Material	Black Nylon 66 with 50% glass fibre
Weight	50g
Dimensions	Length 200mm x Width 36mm (max.) x 26.7mm (max.)

INSTRUCTIONS FOR USE

Removing old sealant beads

Push the pointed end of the tool into the sealant and push forward. Alternatively use the lower point to dig into the sealant and pull towards yourself. Difficult to remove sealant beads can be removed with UniBond Silicone Sealant Remover.

Sealant Smoothing

1. For neat lines, apply masking tape to both sides of the joint.
2. Apply the sealant to the joint, taking care not to apply excessive sealant
3. Select the desired smoothing profile and place the tool at the start of the sealant bead
4. Pressing down firmly, pull the finishing tool at a uniform rate to achieve a perfect finish. Regularly Remove excess sealant collected on the smoother





Cleaning

Use white spirit to clean the smoother if used to smooth silicone or polymer sealants. Otherwise, clean the tool after use with warm soapy water.

LIMITATIONS

Use UniBond Silicone Sealant Remover to aid removal of stubborn silicone sealant residues.

The remover points may be blunted by rough or abrasive surfaces such as mortar, concrete, brickwork

Packaging

Blister card containing 1 x sealant remover & smoother tool

Colour

Black

HEALTH AND SAFETY

Before using the product, please see related Material Safety Data Sheet that is available to download from mysds.henkel.com.

“The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. f.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.”

Henkel Limited

Wood Lane End, Hemel Hempstead, Hertfordshire, HP2 4RQ

Phone: +44 (0) 1606 593 933

Internet: www.henkel.co.uk

email: technical.services@henkel.co.uk