Technical Data Sheet

Technical Data Sheet
Ref: UC6000
Issued: 15.11.2022
Number of pages: 3

UniBond No More Nails Removable Strips

CHARACTERISTICS

UniBond No More Nails Removable Strips are a double-sided die cut pad for removable mounting applications for interior use.

APPLICATION FIELD

UniBond No More Nails Removable Strips will adhere to:
- Metal
- Wood
- Ceramic
- Stone
- Tiles
- Glass
- Many plastics*

*not for use with PE, PP, PTFE (Teflon)

UniBond No More Nails Removable Strips are suitable for non-permanent mounting of:
- Picture frames
- Signs
- Hooks
- Bathroom & Kitchen fixtures

INSTRUCTIONS FOR USE

Application

Apply to clean, dry, smooth, flat surfaces, at least 20mm wide to enable full contact. Apply above +18°C. Do not touch the adhesive or surfaces to which strips are to be applied. In case of painted walls, ensure paint is well bonded to the wall. For best results clean surfaces with methylated sprit. Surfaces must be strong enough to support the weight of the items to be held.

Apply strips without air-bubbles to the substrate and remove yellow protective liner. Press item to be bonded firmly into place. Support heavier items for 24 hours.

Distribute the strips as shown in the diagram to the right.

Maximum holding power of 2.0kg per strip will be reached under ideal conditions: mounting of flat objects (thickness <10mm) to smooth glass or metal surfaces. Direct contact with water can reduce holding power. Final strength is reached after 24h.

For mounting of objects with a thickness >10mm, holding power per strip is reduced. To fix larger objects (thickness >10mm, weight >2kg) use more strips.

How to Remove the Strips

Split the strips by drawing a strong thread behind the mounted object. Care should be taken when removing breakable items. The remaining foam can then be easily peeled off.

TECHNICAL DATA

Colour / Appearance	White foam / double-sided tape
Carrier material	Polyethylene foam
Adhesive	Acrylic
Liner	Yellow Polyethylene/Propylene
Width	20mm
Length	40mm
Gap bridging capacity	Max. 1.0mm
Temperature resistance	-20°C to +95°C (short term)
Application temperature	+18°C to +35°C
Shelf life	24 months from date of manufacture

LIMITATIONS

Storage
Store in a dry, dust free place between 10 C° and 30 °C.

UniBond No More Nails Removable Strips are not suitable for:

- Outdoor use or use in damp/wet areas
- Application to uneven, textured, fibrous dusty or unsound surfaces
- Application to wallpaper
- Mounting mirrors

"The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law."

Henkel Limited
Wood Lane End, Hemel Hempstead, Hertforshire, HP2 4RQ
Phone: +44 (0) 1606 593 933
Internet: www.henkel.co.uk
e.mail: technical.services@henkel.co.uk

This document was created and digitally signed by tdx.henkel.com at 2025-11-28T17:14:12.607Z