



Technical Data Sheet



Technical Data Sheet
Ref: UC6500
Issued: 12.12.2023
Number of pages: 3

UniBond No More Nails on a Roll Interior & Exterior

CHARACTERISTICS

UniBond No More Nails on a roll Interior & Exterior is a double-sided mounting tape with high holding power and high adhesion. UniBond No More Nails on a roll Interior & Exterior has high initial tack and designed for most indoor and outdoor applications. Each roll will hold up to 120kg*



APPLICATION FIELD

- UniBond No More Nails on a roll Interior & Exterior can be used to fix objects on many different smooth surfaces such as wood, ceramic tiles, metal, brick, stone, plaster and many plastics**.
- For interior and exterior applications, waterproof.
- Ideal for mounting applications of mirrors, pictures, frames, signs, hooks, bathroom fixtures, kitchen fixtures, mailboxes, house numbers
- Not recommended for applications on delicate surfaces such as wallpaper, load-bearing or dirt-repellent surfaces.

INSTRUCTIONS FOR USE

Application

Ensure surfaces to be bonded are clean and free of dust, grease or oil. Surfaces should not be load-bearing (Clean surface with alcohol, cleaning benzene or acetone).

Cut tape in the length you need, apply it ensuring no air-bubbles are trapped beneath the tape and remove red protective liner. Press firmly into place.

Avoid application temperatures below 10 °C. Maximum holding power of up to 120kg per roll will be reached under ideal conditions: mounting of flat objects (thickness <10mm) to smooth glass or metal surfaces. Direct contact with water can reduce holding power. Final strength is reached after 24h. The use of smaller pieces than the complete roll will reduce the holding power. On surfaces other than glass or metal, holding power can be reduced. For mounting of objects with a thickness >10mm, holding power is reduced.



TECHNICAL DATA

Colour / Appearance	White foam / double-sided tape
Carrier material	Polyethylene foam
Adhesive	Synthetic rubber
Liner	red Polyethylene/Propylene
Width	19mm
Length	1.5m
Gap bridging capacity	Max. 0.8mm
Temperature resistance	Up to -40°C to +80°C (short term)
Application temperature	10°C to 35°C
Shelf life	24 months from date of manufacture

LIMITATIONS

*Not suitable for the use on PE, PP, PTFE (Teflon)

**Maximum holding power: 120kg per roll under ideal conditions, i.e. mounting smooth, flat objects less than 10mm thick to metal

Not recommended for use on wallpaper or load bearing or dirt-repellent surfaces. If in doubt the tape must be tested in an inconspicuous place.

Permanent adhesion. Mechanical removal required. Bonded items and/ or substrate may be damaged when removing.

Storage

Store in a dry, dust free place between 10 °C and 30 °C.

Packaging

19mm x 1.5 m roll in blister card.

HEALTH AND SAFETY

Before using the product please see related Material Safety Data Sheet that is available on request

“The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.”



Henkel Limited

Wood Lane End, Hemel Hempstead, Hertfordshire, HP2 4RQ

Phone: +44 (0) 1606 593 933

Internet: www.henkel.co.uk

e.mail: technical.services@henkel.co.uk