



Technical Data Sheet



Technical Data Sheet

Ref: UB450

Issued: 14/02/2023

Number of pages: 2

Wall Tile Quick Grout (Cartridge)



CHARACTERISTICS

- Ready to use wall tile grout
- Waterproof
- Easy to apply straight from the cartridge – No mess
- Free smoother tool
- For grouting porcelain and glazed ceramic tiles
- Triple Protection mould resistant – Repels, Prevents, Lasts

APPLICATION FIELD

A ready mixed wall tile grout for porcelain and glazed ceramic wall tiles (up to 6mm joint width), with enhanced mould protection

COMPLIANCE WITH STANDARDS

Henkel Limited is certified by DQS (Certificate Registration number : 003052 QM/UM) as a company operating a Quality Management System to BS EN ISO 9001:2000, BS EN 14001 and OHSAS 18001.

TECHNICAL DATA

| | |
|---------------------------------------|--|
| Composition: | A filled acrylic copolymer emulsion, with fungicide added. |
| Appearance: | White paste. |
| Cure type: | Water evaporation |
| Odour: | Slight odour whilst drying. |
| Density: (g/cm³) | 1.5 |
| pH: | Typically 7.5 - 9.0 |
| Viscosity: | Typically 20,000 - 40,000 poise |
| Application temperature range: | From +5°C to +35°C |
| Coverage: | approx. 2.5m ² |
| Shelf life: | At least 24 months in original sealed packaging. |

Composition and properties of the mixture at 23°C and 50% R.H.

| | |
|-------------------|--|
| Open time: | Approximately 30 minutes. |
| Thermal: | Suitable for service temperature up to 70°C. |
| Fire: | Class F. |



LIMITATIONS

Only for use with porcelain and fully glazed ceramic wall tiles. Do not use with other tile types such as unglazed, satin, matt or metallic detailed tiles.

For interior use only. Not suitable for areas of constant immersion or permanent damp.

If in doubt, contact our technical helpline for further assistance.

STORAGE

Store in cool dry conditions. Protect from frost. Shelf life is at least 24 months in original sealed packaging.

HEALTH AND SAFETY

Before using the product please see related Material Safety Data Sheet that is available on request.

"The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law."

Henkel Limited

Technologies House, Wood Lane End, Hemel Hempstead. HP2 4RQ

Phone: +44 (0) 1606 593 933

Internet: www.henkel.co.uk

email: technical.services@henkel.co.uk